



MAX BOND

PRODUCT DATA SHEET

PH006 OUTDOOR GRASS ADHESIVE

PRODUCT DESCRIPTION

Powerhold Outdoor/Grass Adhesive is a solvent based synthetic grass and external carpet adhesive for outdoor applications. With excellent early bond strength, it prevents edge curling and resists water and weather deterioration.

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants – this includes previously used adhesive and floorcoverings, polishes, paint, waterproofing membranes, concrete curing agents and laitance (laitance being the dusty unstable toppings of poorly or insufficiently cured concrete).

Deep indentations and cracks should be treated with the appropriate cementitious screed in accordance with manufacturer's instructions.

All surfaces must be prepared in accordance with current relevant Australian Standards 1884-2012 Floor Coverings Resilient Sheet & AS2455 including moisture testing.

APPLICATION

Apply adhesive using a "V" notched trowel spreader. Dimensions of notching should be such as to provide a minimum (80%) coverage of adhesive to the back of the floor covering.

As most synthetic grass and fibre bonded carpets have highly textured backings, a deep 3.2 mm to a 6 mm "V" notching is strongly recommended.

For hard to hold carpet, or when installing over low absorbent substrates, it is necessary to allow a longer tack up time.

Always check and ensure good transfer of adhesive to the back of the carpet. Roll within 1 hour of laying.

DO NOT use in rain or if rain is expected during or immediately after laying.

DO NOT allow heavy traffic within 24 hours of installation.

Refer to current AS2455 & AS1884 for further preparation and installation requirements.

CLEAN UP

Clean tools immediately after use with MJS Max Bond SC solvent cleaner.

TYPICAL PROPERTIES

Appearance:	Green Paste
Base:	Synthetic Rubber
Solids:	Approx. 55%
Specific Gravity:	Approx. 1.6
Viscosity:	Creamy paste
Shelf Life:	Up to 1 year from manufacturing date in sealed container at 20°C, out of direct sunlight, undercover and away from all sources of heat and ignition.
Flammable Liquid:	3
Container Size:	1 & 4 Litre metal cans

COVERAGE

Approx. 1.6 m² / Litre when adhesive is evenly spread with a 3.2 mm "V" notched trowel.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS website

Flammable Liquid 3

Updated 11/03/21



QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW
Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA
Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA
Perth
MJS Floorcoverings
Opening soon