



# Cush 'n' Tread

## Premium Carpet Cushion

# SELECT GOLD

### TYPICAL CHARACTERISTIC QUALITIES

- ◆ Quality Cushion = Longer Life. The better the quality of cushion, the longer the life you will get from your floorcovering
- ◆ Suitable for all floor types
- ◆ 100% Australian owned
- ◆ Full Manufacturer's Warranty
- ◆ Excellent thermal & acoustic insulation and dimensional stability
- ◆ Low allergy
- ◆ Unaffected by moisture
- ◆ Environmentally friendly – C.F.C free

|   | AS4288 (Int)-1995 Requirement                               | Method of Testing     | Quality Select Gold SG1080 |
|---|---|-----------------------|----------------------------|
| CLASSIFICATION  |   |                       | RESIDENTIAL                |
| FOAM THICKNESS (mm)   | 12% ±   | AS2111.1              | 10mm ± 0.5                 |
| COLOUR OF FOAM  | N/A   | -                     | MULTI                      |
| LAMINATE COLOUR (PRINTED)   | N/A   | -                     | GOLD                       |
| MESH BLACK  | N/A   | -                     | BLACK                      |
| LAMINATE MICRON   | N/A   | -                     | 25                         |
| BREAKING FORCE LENGTH/WIDTH (N/50mm)  | MINIMUM N40   | AS2001.2.3-1988       | 50/44                      |
| ELONGATION (%)  | 20% MAX EXTENSION FOR APPLIED FORCE OF 40N                  | AS2001.2.3-1988       | 17%                        |
| WORK OF COMPRESSION (J/m <sup>2</sup> ) POST DYNAMIC LOADING                      | MINIMUM 50<br>MAXIMUM 200                                   | APPENDIX A            | 123.4                      |
| MEAN DEFLECTION AT 100 kPa  | MIN 1.5mm MAX 9mm   | APPENDIX A            | 6.22mm                     |
| PERCENTAGE RETENTION OF ORIGINAL W.O.C.   | 40% MINIMUM   | APPENDIX              | 77%                        |
| THICKNESS LOSS:<br>A) STATIC LOADING (24 HRS)<br>B) DYNAMIC LOADING (1000 CYCLES) | MAX 15%<br>MAX 15%  | AS2111.14<br>AS2111.2 | 3.2%<br>7.4%               |
| RESISTANCE TO BREAKING OR CRACKING  | NO CRACKS LONGER THAN 50mm<br>NO CRACKS IN BACKING MATERIAL | APPENDIX B            | PASSED                     |

CUSH 'n' TREAD™ has been trademarked by MJS Underlays. All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Trade Purchasers assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own test. Conditions of Sale contain a limited warranty against manufacturing defects.

#### Roll Dimensions:

**Length: 15 L/m**

**M<sup>2</sup>: 27.45**

**Width : 183 cm**

**Weight: 21 Kg**

**Manufactured by:**  
**Distributed by:**

**MJS Underlays**  
**MJS Floorcoverings**  
PO Box 2393, Mansfield Q 4122  
Ph: (07) 3347-7300  
Fax: (07) 3343-9792

MJS Floorcoverings provides full Technical & Installation Information Services and advice on all Cush 'n' Tread, Cush 'n' Lay, Cush 'n' Wood & Cush 'n' Felt products.

UPDATED 06/08/19

*“Simply The Best”*

[www.mjsfloorcoverings.com.au](http://www.mjsfloorcoverings.com.au)