



Cush 'n' Tread

Premium Carpet Cushion

DURA-WALK DSL

TYPICAL CHARACTERISTIC QUALITIES

- ◆ Quality Cushion = Longer Life. The better the quality of cushion, the longer the life you will get from your floorcovering
- ◆ Double Sided Laminate
- ◆ Unaffected by moisture
- ◆ Environmentally friendly – C.F.C free
- ◆ Excellent thermal & acoustic insulation
- ◆ Low allergy
- ◆ Suitable for all floor types
- ◆ 100% Australian owned
- ◆ Full Manufacturers Warranty

| | AS4288 (Int)-1995 Requirement | Method of Testing | Quality- Dura-Walk DSL DW890 |
|--|---|-------------------|------------------------------|
| CLASSIFICATION | | | RESIDENTIAL |
| FOAM THICKNESS (mm) | 12% ± | AS2111.1 | 8.0mm ± 0.5 |
| COLOUR OF FOAM | N/A | - | GOLD |
| LAMINATE COLOUR | N/A | - | WHITE |
| NON-WOVEN | N/A | - | GOLD |
| LAMINATE MICRON | N/A | - | 25 |
| BREAKING FORCE LENGTH/WIDTH (N/50mm) | MINIMUM N40 | AS2001.2.3-1988 | 54/44 |
| ELONGATION (%) | 20% MAX EXTENSION FOR APPLIED FORCE OF 40N | AS2001.2.3-1988 | 14% |
| WORK OF COMPRESSION (J/m ²) POST DYNAMIC LOADING | MINIMUM 50 MAXIMUM 200 | APPENDIX A | 134 |
| MEAN DEFLECTION AT 100 kPa | MIN 1.5mm MAX 9mm | APPENDIX A | 6.0mm |
| PERCENTAGE RETENTION OF ORIGINAL W.O.C. | 40% MINIMUM | APPENDIX | 79% |
| THICKNESS LOSS: | | | |
| A) STATIC LOADING (24 HRS) | MAX 15% | AS2111.14 | 2.9% |
| B) DYNAMIC LOADING (1000 CYCLES) | MAX 15% | AS2111.2 | 6.9% |
| RESISTANCE TO BREAKING OR CRACKING | NO CRACKS LONGER THAN 50mm NO CRACKS IN BACKING MATERIAL | APPENDIX B | PASSED |

CUSH 'n' TREAD™ has been trademarked by MJS Underlays. All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Trade Purchasers assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own test. Conditions of Sale contain a limited warranty against manufacturing defects.

ROLL DIMENSIONS

LENGTH : 20 L/m

M²: 36

WIDTH: 180cm

WEIGHT: 22.5 Kg

Manufactured by:
Distributed by:

MJS Underlays
MJS Floorcoverings
PO Box 2393, Mansfield Q 4122
Ph: (07) 3347-7300
Fax: (07) 3343-9792

MJS Floorcoverings provides full Technical & Installation Information Services and advice on all Cush 'n' Tread, Cush 'n' Lay, Cush 'n' Wood & Cush 'n' Felt products.

DATA/MJS UNDERLAYS/Specification Sheets – New
UPDATED: 28/08/13

“Simply The Best”