



MAX BOND

PRODUCT DATA SHEET

MAX BOND – CCA

Commercial Carpet Adhesive

PRODUCT DESCRIPTION:

MAX BOND Commercial Carpet Adhesive is water-based carpet adhesive providing a strong tacky film of adhesive that is suitable for bonding carpets, both Double Bond and Direct Stick installations. The adhesive offers a quick grab and has sufficient working time for smaller and larger installations.

FOR BONDING:

MAX BOND Commercial Carpet Adhesive is designed to be used for bonding both dual bond underlay to the subfloor and the carpet to the slab underlay. It is suitable for adhering most Hessian back, Tufted back and woven polypropylene backed carpets

SURFACE PREPARATION:

To be in accordance with the current Australian Standard “Floor Coverings - 1884-2021 Resilient Sheet & Tiles - Laying & Maintenance Practices” or Australian Standard 2455.2.2019 “Textile Floor Coverings – Installation Practice”. All surfaces to be bonded shall be absorbent, dry, smooth, sound and clean. Subfloors must also be free of wax, grease, oil, polishes, old adhesive, curing compounds, high levels of moisture hydrostatic pressure and any other impurities that may affect adhesion.

If mechanical preparation is required, prepare the floor using recommended preparation methods such as shot blasting or diamond grinding, to provide a roughened, clean, sound, and open porous surface. Thoroughly vacuum loose material and dust. The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C.

Max Bond CCA can be applied to concrete substrates with moisture contents up to 85% relative humidity tested with the In-Situ Probe method and can be applied to concrete substrates with pH readings up to 10.0. Test all concrete substrate flooring for moisture content, according to the current Australian Standards prior to priming or the installation of any floorcoverings.

APPLICATION:

Apply adhesive with the recommended notched trowel.

Recommended V Notching

V1 - 1.6mm x 1.6mm Notched Trowel for underlay to subfloor,

V2 - 2.4mm x 2.4mm Notched Trowel for Hessian backed carpets

V3 - 3.2mm x 3.2mm Notched Trowel for Action Bac, woven or highly textured backings.

Apply only the amount of adhesive that can be covered within the open time of the adhesive. Allow adhesive



QUEENSLAND

Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW

Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA

Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA

Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY

Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA

Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA

Perth
MJS Floorcoverings
Opening soon



MAX BOND

PRODUCT DATA SHEET

to develop some initial tack – generally 5-10 minutes at 20°C before lowering the floorcoverings into the Wet Film of adhesive and roll in both directions to ensure transfer has occurred. Tack-up times will depend upon atmospheric conditions and substrate absorbency. Complete the installation according to manufacturer's instructions. Do not allow heavy traffic for 24 hours.

CLEAN UP:

Clean tools immediately after use with warm soapy water.

COVERAGE:

V1 1.6mm x 1.6mm notched trowel will achieve approximately up to 5 square metres per litre.

V2 2.4mm x 2.4mm notched trowel will achieve approximately up to 3 square metres per litre.

V3 3.2mm x 3.2mm notched trowel will achieve approximately up to 2 square metres per litre.

CONTAINER SIZES

15 litre plastic containers

SHELF LIFE / STORAGE:

12 months in unopened containers stored out of direct sunlight. Keep in well ventilated areas stored out of direct sunlight.

NOTES & PRECAUTIONS:

- Drying times can be extended when applied in cold ambient temperatures.
- Don't allow the adhesive to skin over or dry out, it is important the floorcovering being bonded is installed into the Wet film of adhesive
- Don't apply adhesive in direct sunlight.
- Internal use only.

SAFETY & HANDLING

A Safety Data Sheet is available on request.

Product is classified as NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

First Aid

In use, please ensure that Occupational Health and Safety requirements are observed.

Eyes: Irrigate with water for 10 minutes and see a doctor.

Skin: Wash off with warm water and soap.

If swallowed, give plenty of water. Do not induce vomiting. Seek medical attention.



QUEENSLAND

Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW

Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA

Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA

Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY

Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA

Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA

Perth
MJS Floorcoverings
Opening soon



MAX BOND

PRODUCT DATA SHEET

Australian Consumer Law

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

Disclaimer

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: Jan 2022



QUEENSLAND

Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW

Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA

Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA

Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY

Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA

Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA

Perth
MJS Floorcoverings
Opening soon