



MAX BOND

PRODUCT DATA SHEET

ODA

PRODUCT DESCRIPTION:

MJS ODA is an all-weather solvent based (flammable) adhesive specifically formulated for the outdoor installation of non-stretch open weave polypropylene backed synthetic grass carpet as well as most types of needlepunch carpets. Note: Not recommended for urethane and E.V.A. backed carpets.

ODA Carpet Adhesive develops high strength quickly and when cured will withstand unfavourable weather conditions. It will bond securely to cured concrete, asphalt, exterior grade wood and other clean paved surfaces and is ideal for use around swimming pools, balconies, outdoor recreational areas and other applications which are subject to moisture after fixing.

SURFACE PREPARATION:

To be in accordance with the relevant Australian Standards. All surfaces to be bonded shall be absorbent, dry, smooth, sound and clean. Subfloors must also be free of wax, grease, paint, previously used adhesive, polish, PVC based membranes, curing compounds, hydrostatic pressure and any other impurities that may affect adhesion.

The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C. Test all concrete substrate flooring for moisture content, according to the current Australian Standards prior to the installation of any floorcoverings.

APPLICATION:

Spread adhesive with the recommended trowel. Use a V5 or V3 trowel for synthetic grass and a V2 for trowel for needlepunch carpet. Allow adhesive to develop some initial tack – approximately 5-10 minutes at 20°C before lowering the floorcovering into the wet film of adhesive. Note: Do not allow the adhesive to skin over, prior to the lowering the floorcovering into the adhesive film. Roll the floorcovering to ensure 100% transfer of adhesive has occurred onto the backing of the floorcovering.

Complete the installation according to manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roller weight, prior to the adhesive setting. Do not allow heavy traffic for 24 hours. Do not apply adhesive in rain or if rain is expected during or shortly after laying. Note: Apply in a well ventilated area.

SPREAD RATE:

V5 Trowel – Heavy ribbed synthetic grass: Up to 1.5m²/ltr

V3 Trowel – Low ribbed synthetic grass: Up to 2m²/ltr

V2 Trowel – Standard needlepunch backing: Up to 3m²/ltr

Note: Spread rates may vary depending on the condition and substrate absorbency.



QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW
Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA
Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA
Perth
MJS Floorcoverings
Opening 2019



MAX BOND

PRODUCT DATA SHEET

HIGHLY FLAMMABLE:

Avoid contact with skin and eyes and avoid breathing vapour.
Contains: 30-60% Liquid Hydrocarbons

CLEAN UP:

To clean up equipment and adhesive spills, use with care a suitable cleaner/thinner (Flammable solvent). However, it is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

CONTAINER SIZES:

20 litre containers

SHELF LIFE / STORAGE:

12 months in unopened containers stored out of direct sunlight. Keep container tightly closed. Store Locked up. Keep container in a cool well ventilated place away from sources of heat.

SAFETY & HANDLING:

A Safety Data Sheet is available on request. Keep away from HEAT/SPARKS/OPEN FALMES/HOT SURAFCES – NO SMOKING. Keep container tightly closed. Avoid contact with skin and eyes and avoid breathing vapour. Ground/bond container and receiving equipment. Use explosion proof electrical /ventilation/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Avoid breathing vapours. Use only outdoors or in well ventilated areas. Wear protective gloves, eye and face protection. Wash thoroughly after handling. Person who are sensitive to odours and or chemicals should avoid the work area. During the installation process, adequate ventilation of the work area should be maintained. Do not handle until Safety Directions have been read and understood.

FIRST AID:

For advice or you feel unwell contact a Poisons Information Centre (Australia ph 131126, New Zealand ph 0800 764 766) or a doctor at once. If swallowed do NOT induce vomiting. If swallowed immediately call the Poisons Information centre or a doctor. IF ON SKIN Remove immediately all contaminated clothing and wash skin with soap and water. If skin irritation occurs get medical advice/attention. IF IN EYES Rinse carefully with water for several minutes. If eye irritation persists get medical advice/attention. Wash contaminated clothing before reuse. IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing.



QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW
Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA
Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA
Perth
MJS Floorcoverings
Opening 2019



MAX BOND

PRODUCT DATA SHEET

FIRE:

IN case of FIRE use foam to extinguish. Firefighters should wear full protective clothing and self contained breathing apparatus.

DISCLAIMER:

All Statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Issued: January 2021



QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW
Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA
Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA
Perth
MJS Floorcoverings
Opening 2019