

MJS Silicone XW Centre Bead Tape

RLA Polymers Pty Ltd

Version No: 2.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: **03/08/2017** Print Date: **07/09/2017** S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	MJS Silicone XW Centre Bead Tape				
Synonyms	Not Available				
Other means of identification	Not Available				

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
Relevant identified uses	A multipurpose tape with silicone release backing for use on primary and secondary backed carpets.

Details of the supplier of the safety data sheet

Registered company name	RLA Polymers Pty Ltd		
Address	215 Colchester Road Kilsyth VIC 3137 Australia		
Telephone	st 3 9728 1644		
Fax	+61 3 9728 6009		
Website	www.rlagroup.com.au		
Email	sales@rlagroup.com.au		

Emergency telephone number

Association / Organisation	Not Available	
Emergency telephone numbers	s +61 3 9726 1644 (RLA Group Technical Manager) business hours e	
Other emergency telephone numbers		

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable		
Classification	Not Applicable		
Label elements			
Hazard pictogram(s)	Not Applicable		
SIGNAL WORD	NOT APPLICABLE		

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
		blend of hydrocarbon wax, resin and ethylenevinyl acetate	
		polymer on fibre glass and paper	
Not Available	>90	Ingredients determined not to be hazardous	

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.	
Skin Contact	Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. In case of burns: Immediately apply cold water to burn either by immersion or wrapping with saturated clean cloth. DO NOT remove or cut away clothing over burnt areas. DO NOT pull away clothing which has adhered to the skin as this can cause further injury. DO NOT break blister or remove solidified material. Quickly cover wound with dressing or clean cloth to help prevent infection and to ease pain. For large burns, sheets, towels or pillow slips are ideal; leave holes for eyes, nose and mouth. DO NOT apply ointments, oils, butter, etc. to a burn under any circumstances. Water may be given in small quantities if the person is conscious. Alcohol is not to be given under any circumstances. Reassure. Treat for shock by keeping the person warm and in a lying position. Seek medical aid and advise medical personnel in advance of the cause and extent of the injury and the estimated time of arrival of the patient.	
Inhalation	If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.	
Ingestion	If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.	

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Do NOT direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.
- Water spray or fog.
- ▶ Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid reaction with oxidising agents			
Advice for firefighters				
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area. 			
Fire/Explosion Hazard	Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Other combustion products include: , carbon dioxide (CO2)			
HAZCHEM	Not Applicable			

MJS Silicone XW Centre Bead Tape

Print Date: 07/09/2017

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up.
Major Spills	Clear area of personnel. Alert Fire Brigade/Emergency Services and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment. Prevent, by any means available, spillage from entering drains or watercourses.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	The greatest potential for injury caused by molten materials occurs during purging of machinery (moulders, extruders etc.) It is essential that workers in the immediate area of the machinery wear eye and skin protection (such as full face, safety glasses, heat resistant gloves, overalls and safety boots) as protection from thermal burns. Fumes or vapours emitted from hot melted materials, during converting operations, may condense on overhead metal surfaces or exhaust ducts. The condensate may contain substances which are irritating or toxic. Avoid contact of that material with the skin.
Other information	Keep dry. Store under cover. Store in a well ventilated area. Store away from sources of heat or ignition. Avoid heat gt;50C.

Conditions for safe storage, including any incompatibilities

Metal can or drum Suitable container Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.		Packaging as recommended by manufacturer.
	Storage incompatibility Avoid storage with oxidisers	

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Motorial name

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

ingredient	wateriai riairie	IEEL-I	IEEL-Z	IEEL-3
MJS Silicone XW Centre Bead Tape	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
ingrouient	Not Available		Nevious IDEN	
Ingredients determined not to be hazardous			Not Available	

TEEL 1

Exposure controls

Provide adequate ventilation in warehouse or closed storage areas. Appropriate engineering controls Provide mechanical ventilation; in general such ventilation should be provided at compounding/converting areas and at fabricating/filling work stations where the material is heated. Local exhaust ventilation should be used over and in the vicinity of machinery involved in handling the molten material. Personal protection

Eye and face protection

- Safety glasses.
- Safety glasses with side shields
- Chemical goggles.
 - Full face shield may be required for supplementary but never for primary protection of eyes.
 - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Page 4 of 6 Issue Date: 03/08/2017 Version No: 2.1.1.1 Print Date: 07/09/2017

MJS Silicone XW Centre Bead Tape

Skin protection	See Hand protection below
Hands/feet protection	Wear physical protective gloves, e.g. leather. Wear safety footwear. When handling hot or molten liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. Usually handled as molten liquid which requires worker thermal protection and increases hazard of vapour exposure. CAUTION: Vapours may be irritating.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: Overalls. Barrier cream. Eyewash unit.
Thermal hazards	Not Available

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Orange waxy beads of hot melt spread on a fibre glass scrim with a brown silicone backed crepe paper backing.		
Physical state	Manufactured	Relative density (Water = 1)	0.97
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	>180
Melting point / freezing point (°C)	80-120	Viscosity (cSt)	10000 cPs @ 180C
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>200	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Not normally a hazard due to non-volatile nature of product High concentration of vapour from molten hot melt may cause irritation.
Ingestion	Not normally a hazard due to the physical form of product. The material is a physical irritant to the gastro-intestinal tract
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Molten material is capable of causing burns.
Eye	Not normally a hazard due to physical form of product. High concentration of vapour from molten hot melt may cause irritation.
Chronic	Generally not applicable. Repeated or prolonged contact of the tape or solid hot melt with the skin may cause irritation. Repeated or prolonged breathing of the vapours of the molten hot melt may cause an allergic response and induce asthma-like sensitisation.

Page 5 of 6 Issue Date: 03/08/2017 Version No: 2.1.1.1 Print Date: 07/09/2017

MJS Silicone XW Centre Bead Tape

MJS Silicone XW Centre Bead	TOXICITY	IRRITATION	
Таре	Not Available	Not Available	
Legend:	Value obtained from Europe ECHA Registered Substance	s - Acuto toxicity 2 * Value obtained fr	manufacturar's SDS Links athonuics enacified data
Legena.	extracted from RTECS - Register of Toxic Effect of chemical	,	on manulacurers 3003. Onless ourerwise specified data
Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	\circ	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0
		Logond: V	- Data available but does not fill the criteria for classification

 Data available to make classification

- Data available to make classification O - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

MJS Silicone XW Centre Bead Tape	ENDPOINT Not Available	TEST DURATION (HR) Not Available	SPECIES Not Available	VALUE Not Available	SOURCE Not Available
Legend:	(QSAR) - Aquat		Registered Substances - Ecotoxicological Information Ecotox database - Aquatic Toxicity Data 5. ECETOC . centration Data 8. Vendor Data	, ,	

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- ▶ Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

MJS Silicone XW Centre Bead Tape

Safety, health and environmental regulations / legislation specific for the substance or mixture

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	Υ
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

 ${\sf PC-TWA}$: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index