



Cush 'n' Tread

Premium Carpet Cushion

PROJECT

TYPICAL CHARACTERISTIC QUALITIES

- ◆ Double sided laminate
- ◆ Quality Cushion = Longer Life. The better the quality of cushion, the longer the life you will get from your floorcovering
- ◆ Unaffected by moisture
- ◆ Environmentally friendly – C.F.C free
- ◆ Dimensional stability
- ◆ Excellent thermal & acoustic insulation
- ◆ Low allergy
- ◆ Suitable for all floor types
- ◆ 100% Australian owned
- ◆ Full Manufacturers Warranty

	AS4288 – 2003	Method of Testing	Quality – Project P7140
CLASSIFICATION			HEAVY COMMERCIAL
FOAM THICKNESS (mm)	12% ±	AS4288 – 2003	7mm ± 0.5
FOAM DENSITY KG'S/M ³	N/A		140 (NOMINAL)
COLOUR OF FOAM	N/A		GOLD / MULTI
TOP LAMINATE COLOUR (PRINTED-MJS LOGO)	N/A		WHITE
NON-WOVEN	N/A	-	ORANGE
LAMINATE MICRON	N/A		25
BREAKING FORCE LENGTH/WIDTH (N/50mm)	MINIMUM N40	ISO 9073-3 1989	87 / 46
ELONGATION (%)	20% MAX EXTENSION FOR APPLIED FORCE OF 40N		8.1%
WORK OF COMPRESSION (J/m ²) POST DYNAMIC LOADING	MINIMUM 50 MAXIMUM 200	APPENDIX A	172.2 / 160.4
MEAN DEFLECTION AT 100 kPa	MIN 1.5mm MAX 9mm	APPENDIX A	4.2mm
PERCENTAGE RETENTION OF ORIGINAL W.O.C.	40% MINIMUM	APPENDIX	93%
THICKNESS LOSS: A) STATIC LOADING (24 HRS) B) DYNAMIC LOADING (1000 CYCLES)	MAX 15% MAX 15%	AS NZS AS2111.1 – 1996	2.5% 1.4%
RESISTANCE TO BREAKING OR CRACKING	NO CRACKS LONGER THAN 50MM. NO CRACKS IN BACKING	APPENDIX B	COMPLIES
FIRE PROPAGATION PROPERTIES	-	AS/ISO 9239.1 2003	COMPLIES
IMPACT NOISE REDUCTION (1000HZ)	-	ISO 140/8	52
VOC EMISSION TEST	Green Building Council of Australia	CRI & GREEN STAR	COMPLIES
SIMULTANEOUS DETERMINATION OF IGNITABILITY, FLAME PROPOGATION, HEAT RELEASE AND SMOKE DEVELOPMENT RATE			Mean Critical Radiant Flux = 8.0 kw/m ² Mean Smoke Development Rate = 178% /min

CUSH 'n' TREAD™ has been trademarked by MJS Underlays. All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Trade Purchasers assume all risk and liability resulting from the use of this product and must confirm the suitability thereof by their own test. Conditions of Sale contain a limited warranty against manufacturing defects.

Roll Dimensions:

Length: 15 L/m

M²: 27

Width : 180 cm

Weight: 27 Kg

Manufactured by:
Distributed by:

MJS Underlays
MJS Floorcoverings
PO Box 2393, Mansfield Q 4122
Ph: (07) 3347-7300
Fax: (07) 3343-9792

MJS Floorcoverings provides full Technical & Installation Information Services and advice on all Cush 'n' Tread, Cush 'n' Lay, Cush 'n' Wood & Cush 'n' Felt products.

DATA/MJS UNDERLAYS/Specification Sheets – New
UPDATED: 28/08/13

“Simply The Best”