AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

TEST REPORT

Test Number:

Issue Date

Print Date

23-001133

6/04/2023

6/04/2023

Client: Tarkett Australia Pty Ltd

Suite 1 Level 3 3 Columbia Court

Baulkam Hills NSW 2153

Sample Description Clients Ref : "Somplan 100"

Compaq Vinyl
Colour: Grey

End Use: Floorcovering

Nominal Composition: Vinyl with PUR surface treatment Nominal Mass per Unit Area/Density: 3200g/m2

Nominal Thickness: 2mm



292916 63671 Page 1 of 2

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.





AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

TEST REPORT

Client: Tarkett Australia Pty Ltd

Suite 1 Level 3 3 Columbia Court

Baulkam Hills NSW 2153

Test Number : 23-001133

Issue Date : 6/04/2023
Print Date : 6/04/2023

AS 4586-2013 Appendix A Slip Resistance Classification of new Pedestrian Surface Materials Wet Pendulum Test Method

Date of Testing 06/04/2023

Test Temperature (20±5degC) 21 °C

Sample Preparation Sample washed with pH neutral detergent and

dried

Test Direction Length

Fixed/Unfixed Unfixed

Slider No 96 Batch No 15

Length 1 2 3 4 5 SRV British Pendulum 32 33 33 33 33 33

Number

Classification P2

Equipment: Cooper Pendulum Skid Tester Serial No: 1433-01 Calibrated 21/09/2021 Slider prepared using P400 and 3µm lapping film.

These results apply only to the specimens tested and it is recommended that before selection of flooring or paving materials the effect of service conditions, including maintenance and wear on their slip resistance be checked.

292916 63671 Page 2 of 2

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



MICHAEL A. JACKSON B.Sc.(Hons)

Fiona McDonald

APPROVED SIGNATORY